





F-MARK2 AUTO SHEET FEEDER

BLADES

| | | | |
|---|---------------|---------------------------------|--|
|  | CB09UB | Angle 45° Diameter 0.9mm | Standard blade for vinyl cutting & self-adhesive marking film (PVC film) up to 0.25 mm thick. Maximum cutting distance is approx. 13,123 ft. |
|  | CB15U | Angle 45° Diameter 1.5mm | Supersteel blade for cutting rigid or thicker media, 0.25 mm to 0.5 mm thick. (laminates, smart device, device screen protection media) |

F-MARK2 AUTO SHEET FEEDER

BLADE HOLDERS

| | | |
|---|---|--|
|  | PHP33-CB09N-HS SPRING BUILT-IN TYPE | Compatible with Blades: CB09UA • CB09UA-K60 • CB09UB • CB09UB-K60 0.9mm, blue top, black ABS tip. Not recommended for CB09UA blades with springs. |
|  | PHP33-CB15N-HS SPRING BUILT-IN TYPE | Compatible with Blades: CB15U • CB15U-K30* • CB15UA • CB15U-K20-2SP • CB15UA-K30 • CB15UB 1.5mm**, red top, black ABS tip. |
|  | PHP35-CB09-HS SPRING BUILT-IN TYPE | Compatible with Blades: CB09UA • CB09UA-K60 • CB09UB • CB09UB-K60 0.9mm, blue top, black brass tip. ATTENTION: If you are using CB09UA Blade (with spring); Insert only the CB09UA blade without the spring. This blade-holder, plunger design already includes an internal spring. These brass tip blade-holders, plungers are more rigid and lend to more accurate cutting. |
|  | PHP35-CB15-HS SPRING BUILT-IN TYPE | Compatible with Blades: CB15U • CB15U-K30* • CB15UA • CB15U-K20-2SP • CB15UA-K30 • CB15UB 1.5mm**, red top, black brass tip. These brass tip blade-holders/plungers are more rigid & lend to more accurate cutting. NOTE: REMOVE CB15 SP Blade spring before installing into this Blade-holder. DO NOT install any blade spring to more accurate cuts. |

Recommended Setting On Control Panel for Small Detailed Figure and Character Cutting:
CB15U-K30 Offset +31, Force 10-14, Speed 30 or less, Acceleration 2

CE7000-40, 60 and 120 Plus only. *CB15U-K30 can not be selected as the tool type.
Please select (OTHER) instead.