

FCX2000 SERIES

BLADES

	CB09UB	Angle 45° Diameter 0.9mm	Standard blade for vinyl cutting & self-adhesive marking film (PVC film) up to 0.25 mm thick. Maximum cutting distance is approx. 13,123 ft.
	CB09UB-K60	Angle 30° Diameter 0.9mm	Supersteel Blade for cutting the window tint film or thin film, up to 0.25 mm thick.
	CB15U	Angle 45° Diameter 1.5mm	Supersteel blade for cutting rigid or thicker media, 0.25 mm to 0.5 mm thick. (laminates, smart device, device screen protection media)
	CB15U-K30	Angle 60° Diameter 1.5mm	Supersteel Blade for cutting rigid media, 0.25 mm to 0.5 mm thick. And also small detailed characters on marking film (up to 0.25mm). Recommended blade for sandblast rubber resist media cutting and Avery Series of Reflective sheeting.
	CB15UA	Angle 45° Diameter 1.5mm	Supersteel Blade for cutting high-intensity reflective film or harder film.
	CB15UA-K30	Angle 60° Diameter 1.5mm	Supersteel Blade for cutting rigid media, 0.25 mm to 0.5 mm thick. And also small detailed characters on marking film (up to 0.25mm). Recommended blade for sandblast rubber resist media cutting and Avery Series of Reflective sheeting.
	PM-CB-001	Angle 60° Diameter 3mm	Supersteel blade for cutting thick rigid materials such as corrugated paper up to E flute or chip board up to 2 mm thick.
	CB30UC	Angle 45° Diameter 3mm	Super steel blade for cutting thick rigid material such as cardstock and chip board up to 2mm

FCX2000 SERIES

BLADE HOLDERS

	PHP31 FIBERSTEADTLER	FIBERSTEADTLER Lumocolor Fiber Tip Pen Holder.
	PHP33-CB09N-HS SPRING BUILT-IN TYPE	Compatible with Blades: CB09UA • CB09UA-K60 • CB09UB • CB09UB-K60 0.9mm, blue top, black ABS tip. Not recommended for CB09UA blades with springs.
	PHP33-CB15N-HS SPRING BUILT-IN TYPE	Compatible with Blades: CB15U • CB15U-K30* • CB15UA • CB15U-K20-2SP • CB15UA-K30 • CB15UB 1.5mm**, red top, black ABS tip.
	PHP34-BALL	Compatible with Blades: CB30UC-1 • PM-CB-001
	PHP35-CB09-HS SPRING BUILT-IN TYPE	Compatible with Blades: CB09UA • CB09UA-K60 • CB09UB • CB09UB-K60 0.9mm, blue top, black brass tip. ATTENTION: If you are using CB09UA Blade (with spring); Insert only the CB09UA blade without the spring. This blade-holder, plunger design already includes an internal spring. These brass tip blade-holders, plungers are more rigid and lend to more accurate cutting.
	PHP35-CB15-HS SPRING BUILT-IN TYPE	Compatible with Blades: CB15U • CB15U-K30* • CB15UA • CB15U-K20-2SP • CB15UA-K30 • CB15UB 1.5mm**, red top, black brass tip. These brass tip blade-holders/plungers are more rigid & lend to more accurate cutting. NOTE: REMOVE CB15 SP Blade spring before installing into this Blade-holder. DO NOT install any blade spring to more accurate cuts.
	PHP34-CB30-HS	Compatible with Blades: CB30UC-1 • PM-CB-001
	PHP71-SHARPIE	Sharpie Pen holder with a metal sleeve that can be used with our FC & CE Cutters

Recommended Setting On Control Panel for Small Detailed Figure and Character Cutting:
CB15U-K30 Offset +2, Force 10-14, Speed 30 or less, Acceleration 3

FCX2000 SERIES

CREASING TOOLS

	CP-001 	Stick Type Creasing Tool for heavy paper
	CP-002 	Roller Type Creasing Tool for cardboard
	CP-003 	Roller Type Creasing Tool for corrugated board
	PM-CT-002 	Pen Type Creasing Tool for curves on heavy paper
	CPGA-011	Creasing tool with 0.03" fine tip for creasing paper
	CPGA-012	Creasing tool with 0.05" tip for creasing cardboard